

T4S6DX-M6-L

Product Feature :

- * Supports the wired or wireless transmission mode
- * H.265, 4 million ultimate effects
- * 4MM gun for panoramic view, 6MM ball for details
- * Single IP dual channel technology allows for simultaneous preview of both fixed-point and moving point dual channel live footage
- * Support AI humanoid detection, humanoid tracking, and sound and light alarm
- * Low noise sensor+F1.6 large aperture, making nighttime picture quality more transparent
- * Built-in pickups, Two-way intercom, External high-power speaker, Voice deterrence reminder
- * Support for TF card storage, Full day video storage about 20-25G



Chip parameters	
Model	T4S6DX-M6-L
Product Name	4.OMP Smart Linkage WIFI PTZ Camera
System structure	Embedded Linux, single core 32-bit DSP, pure hard compression, watchdog, 8MB FLASH, 64MB built-in DDR
sensor	4 million pixel CMOS (lens optical size: 1/3 "), color 0.001Lux@F1.2 (AGC ON), Black and White 0Lux (IR ON) 4 million pixel CMOS (lens optical size: 1/2.7 "), color 1.0Lux@F2.0 Black and white 0.1 Lux@F2.0 ;
Video Process	H. 265+/H.265/H.264 video encoding, supports dual stream, supports stream speeds adjustable from 200 to 8000kbps
Frame Rates	4 million pixels 20 frames , adjustable from 7 to 20 frames/second, 2 million pixels at 20 frames , adjustable 7 to 20 frames/second
Image Output	4 million pixel main stream: 2560x1440@2304 × 1296@1080P; 4 million pixel main stream: 2560x1440,2304 × 1296,1080P
	Substream: 640 × 360, 352 × 288
Audio Processing	G. 711 encoding and decoding standard, supports two-way voice intercom function, supports audio and video synchronization
Network protocols	Support TPS, TCP/IP, IPv4, DHCP, RTSP, P2P
Business Functions	Supports OSD, real-time video transmission, intelligent detection and alarm linkage, and SEETONG cloud services
Client	Support mobile app "SEETONG" for iOS, Android client, and PC client
Other Functions	Support AI humanoid detection, humanoid tracking, and sound and light alarm, Red and blue light alarm, one click automatic calibration, 6x digital zoom
External Parameters	
Supplement Light	Fixed point gun with 4 white lights and 4 infrared lights, moving point ball with 6 infrared lights and
External Storage	With TF storage slot, support max to 512GB
External Ports	1*RJ45 Ethernet interface, 10/100M self-adaption, 8KV anti-static electric capacity;
Lightning	Power supply comprehensive lightning protection, through the ITU-T, K.21-2008, IEC61000-4-2/IEC61000-4-5
Power supply	DC12V-2A Power input interface
Operating	-20℃~+55℃
Operating	IP65

Power Consumption	Day \leq 4.2W Max Night \leq 6.6W Max
Size (mm)	Sphere is 190mm*210mm*290mm
Weight	NW:1610g; GW:1910g



Seetong
official product administration Europe