

**SEETONG MEXICO S.A.S de C.V. ANALZINGO 16, COL. ANALCO, CUERNAVACA,
MORELOS, MEXICO, CP 62166 RFC SME250225DB3 TEL +52 9986946706**

MODELO IPV-SW-9013-SL 4mp

DUAL LENTE 18X IP PTZ IA IP65 SDK 32g POE

ARTÍCULO CON PARTIDA ARANCELARIA HS 85258003

MATERIAL: METAL CON ALIANZA

PAÍS DE ORIGEN: HECHO EN CHINA

COLOR DE LA CÁMARA: BLANCO

**ACCESORIOS: HARDWARE DE SOPORTE, BRAZO DE SUJECCIÓN ARTICULADO,
MANUAL DE USUARIO**

USO: VIDEOVIGILANCIA CIRCUITO CERRADO DE TELEVISION

CAPACIDAD: ONVIF IP de 6MP

MARCA: SEETONG

FORMATO DE VÍDEO PAL/NTFS

PESO Y MEDIDAS DEL PAQUETE 26X26X40 6.7KG

CARACTERISTICAS

SEETONG MEXICO S.A.S de C.V. ANALZINGO 16, COL. ANALCO, CUERNAVACA,
MORELOS, MEXICO, CP 62166 RFC SME250225DB3 TEL +52 9986946706



Specs	
DSP	ST377+200AI+400AI
Sensor	PTZ camera
	1/2.8 CMOS 4.0MP
Video output	2304*1296
Lens	36倍 5.35-96.3mm
VOA	W:53.9°; P: 44.3°; T:33.9° Tele :9° ; P: 7.8°; T:5.8°
DNR	2DNR,3DNR
Aperture	F1.8~F2.5

SEETONG MÉXICO S.A.S de C.V. RFC SME250225DB3 ANALZINGO 16, COL ANALCO,
CUERNAVACA, MORELOS, MEXICO, CP 62166 TEL +52 9986946706

**SEETONG MEXICO S.A.S de C.V. ANALZINGO 16, COL. ANALCO, CUERNAVACA,
MORELOS, MEXICO, CP 62166 RFC SME250225DB3 TEL +52 9986946706**

Image setting	auto W/B /AE/ BLC/ DWDR/ Digital anti-fog/ anti-flash
Video compression	H.265AI dual stream ,AVI ; bitrate 0.1M~10Mbps adjustable ; fram rate 1~30 fp/s adjustable
Audio	Two way audio, build in Mic and speaker
Preset Points	Support preset setting
Tour	Support 1 tour (max 1-16 presets)
Rotation Speed	Pan 270°, 22°/S , Tilt 90°, 15°/s
AI function	human detection,human tracking,intrusion detection,line crossing alarm
Alarm linkage	TF card local video recording, APP push alarm , sound and light alarm
APP	Seetong, Support Android、IOS mobile remote management
Operation menu	Multi language, English, German, Spanish, French,Italian, Japanese, Korean, Polish, Portuguese, Russian, Thai, Turkish, Vietnamese, Simplified Chinese, Traditional Chinese
Communications Protocol	RTSP/FTP/DHCP/NTP/UPnP/(not support onvif, can connected to the XM NVR)
Wired connector	RJ45 connector , 10/100M adaptive
	HOME DEVICE FREE BAND
IR distance	Up to 150meters
Warm light distance	Up to 150meters
LEDs	9pcs Dual Wick Lamps (fixed camera) 2pcs IR+9pcs warm light (PTZ camera)
Light mode	Colorful Mode, IR Mode, Intellegent Mode
Factory default	Support button reset
Operating temperature	-25℃~+50℃
Power	12V DC
Consumption	≤20W

WEIGHT AND MEASUREMENTS OF THE PACKAGING

26X26X40 WEIGHT 7KG IN COLOR CARDBOARD BOX

**SEETONG MÉXICO S.A.S de C.V. RFC SME250225DB3 ANALZINGO 16, COL ANALCO,
CUERNAVACA, MORELOS, MEXICO, CP 62166 TEL +52 9986946706**

**SEETONG MEXICO S.A.S de C.V. ANALZINGO 16, COL. ANALCO, CUERNAVACA,
MORELOS, MEXICO, CP 62166 RFC SME250225DB3 TEL +52 9986946706**



SUPORT P2P FOR IOS Y ANDROID

TUTORIALES

