



IPV-N1032QR-EHL

FICHA TÉCNICA SEETONG

Modelo y partida arancelaria

IPV-N1032QR-EHL 32CH 4SATA IA FACE RECOGNITION 512 MPS HS 85229000

Seetong México
administracion@seetong.mx

FICHA TÉCNICA



Detección y reconocimiento de rostros / Detección de peatones / Detección de vehículos / Conteo cruzado / Mapa de calor / Detección de densidad de multitudes / Detección de intrusión perimetral / Detección de cruce de línea / Detección de longitud de cola / Detección de matrículas / Detección de sonidos raros

Model Name IPV-N1032QR-EHL IPV-N1032GR-EHL

Video Resolution 8MP,5MP, 3MP ,2MP(1080P),1.3MP(960P),1.0MP(720P)

Recording Bandwidth Inputs 640M

out 640M

Performance

Live/Playback Compression Audio: G.711a

Video : H.264/H.265/H.264+/H.265+

Frame rate 4K:240fps

4MP:480fps

2MP:960fps

Event MD(Sensitivity Level 1~8)

Videlo loss

Beep, Email,

FICHA TÉCNICA

Push notification to Mobile APP

Playback function Fast forward / backward (2x, 4x, 8x,16x)

Slow forward (1/2x, 1/4x, 1/8x,1/16x)

Playback Max 16CH playback

Fisheye Support

UI/MonitoringLocal UI5.0

WEB IE10/11

Safari V12.1 above

Firefox V.52 above

Google chrome V.57 above

Edge V.79 above

Mobile viewer Rxcamview

Push Notification TUTK/RS

AI Face Detection

Pedestrian Detection

Vehicle Detection

Cross Counting

Heat Map

Crowd Density Detection

Perimeter Intrusion Detection

Line Crossing Detection

Queue Legth Detection

License Plate Detection

Rare Sound Detection

Interface

P/W Reset YES

Monitors HDMI 2 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 ,
1600*1200, 1920*1200, 3840*2160/EDID) Async out

FICHA TÉCNICA

Ethernet 2 RJ45 1000 Base-T

USB USB2.0*1(front)

USB3.0*2(rear)

Audio out 1

E-sata 1

HDD 4 SATA HDD, up to 12TB 2 SATA HDD, up to 12TB

Line in 1

RS485 1

Alarm Input/out 16in /1out

General

OSD Language English/French/Spanish/Portuguese/German/Italian/Greek/Danish

/Finnish/Russia/Hebrew/Turkish/Bulgarian/Arabic/Korean/

Japanese/Thai/Hindi/Romanian/Dutch/Polish

Mechanical design Dimension (WxDxH) 378*325.8*66mm 380*340*50mm

Electrical Input Voltage/Current 12V/5A

Power consumption (excluding hard disk) 8W

Environmental Operating Temperature/Humidity Temperature : -10°C~+50°C
(14°F ~ 122°F)

Humidity : Less than 90%RH