

8 Port Full Gigabit POE Switch-(8+2)

Model No.:IPV-HSGQ08G20GB

Product Describe

The PoE switch provides power and data from a single point, using Power over Ethernet (PoE) over a single Cat-5 cable. It can be used for any 10/100/1000Mbps link and supply industry-standard IEEE 802.3af/at power. Advanced auto-sensing algorithm gives power to 802.3af end devices, In addition, the PoE switch automatically determines PoE requirements, speed, duplex, and cable type using Auto Uplink. Easy to operate and reliable.

The PoE switch is ideal for powering PoE devices such as IP cameras, WLAN access point, IP phones, office access control systems, and other PD devices and offers a line of high quality products that provide a total solution for Ethernet application in different environments.

8 Port Full Gigabit POE Switch(8+2)



- ◆ 8*1000mbps RJ45 POE port,UP-Link 2*1000m RJ45 port
- ◆ 100m Transmission Distance,1-8 port support VLAN mode
- ◆ Compatible with IEEE802.3AF/AT
- ◆ Whole Power:120W
- ◆ All port supported by MDI/MDIX auto flip and self negotiation
- ◆ Supply 8pcs 10/100/1000Mbps adaptive high speed forwarding data packet non-lost port.
- ◆ Each port max. power supply reached 30W.
- ◆ Low heat design, safe and reliable, high stability
- ◆ Application:◆ Wireless Access Point◆ IP Camera◆ IP Phone◆ Computer Networks

Technical Specification

Product Name	8 Port Full Gigabit POE Switch(8+2)
Product Model	08G20GB
DATA PIN	1/2+ 3/6- ,4/5+ 7/8-
Power Supply Type	Build In, 1/2+,3/6-
Max. PoE Power for single port	30W
Connector	8*1000mbps POE port,2*1000mbps Uplink port
Network Medium	Cat5 (UTP) or more
Technology	
Network Standards	IEEE 802.3i 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3z、IEEE 802.3ab 1000BASE-T IEEE 802.3x Flow Control IEEE 802.3af/at Power over Ethernet
PoE power	30W per port(IEEE802.3af/at). Wiring: power provided over pairs 1/2 and 3/6

FICHA TECNICA POR SWITCH

Processing types	Store-and-forward Half-duplex back pressure and IEEE 802.3x full-duplex flow control
Address database Table Size	2K MAC address
Buffer memory	48Kb embedded memory per unit
Backboard Bandwidth	20Gpbs Full duplex
Network Latency	Less than 20us for 64 byte frames in store-and-forward mode for 1000Mbps to 1000Mbps transmission
Power	
Input	AC 110-240 V, 50/60 Hz
PoE power consumption	30W per port(IEEE802.3af/at)
Overload current protection	Present
Mechanical	
Casing	Metal
Installation	Wall mounting/ Desktop
Interface	
LED Indicators	System: Power, PoE Maximum power Per port: Link, Activity, Speed, PoE active, PoE error
Environment specification	
Operating temperature	-10-55℃
Storage temperature	-40-70℃
Operating humidity	90% maximum relative humidity, non-condensing
Storage humidity	95% maximum relative humidity, non-condensing
Regulatory Approval	
ISO	Manufactured in ISO9001 facility
Safety	CE/CCC/FCC
Warranty	2 Years
Dimensions	202*140*45mm (L*W*H)
Weight	N.W:0.9Kg G.W:1.1Kg

Package List

Package List	8 Port Full Gigabit POE Switch(8+2) *1
	User Guide*1
	Warranty Card*1
	Power cable*1

Product Details

FICHA TECNICA POR SWITCH

**Application Diagram**

